

Zdjęcie jest reprezentatywne

Eaton 189906

Eaton Moeller® series PKZM0 Motor-protective circuit-breaker (-EA), 3p, Ir=16-20A, screw connection

General specifications

PRODUCT NAME	Eaton Moeller® series PKZM0 Motor-protective circuit-breaker
CATALOG NUMBER	189906
EAN	4015081879021
PRODUCT LENGTH/DEPTH	76 mm
PRODUCT HEIGHT	93 mm
PRODUCT WIDTH	45 mm
PRODUCT WEIGHT	0.296 kg
COMPLIANCES	CE Marked RoHS conform
MODEL CODE	PKZM0-20-EA

Features & Functions

ACTUATOR TYPE	Turn button
FEATURES	Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102)
FUNCTIONS	Phase failure sensitive
NUMBER OF POLES	Three-pole

General

CONNECTION	Screw terminals
LIFESPAN, ELECTRICAL	100,000 operations
LIFESPAN, MECHANICAL	100,000 Operations
MOUNTING POSITION	Can be snapped on to IEC/EN 60715 top-hat rail with 7.5 or 15 mm height.
OPERATING FREQUENCY	40 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Motor protective circuit breaker
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SHOCK RESISTANCE	25 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
SUITABLE FOR	Branch circuit: Suitable for group installations, (UL/CSA) Also motors with efficiency class IE3
TEMPERATURE COMPENSATION	-5 - 40 °C to IEC/EN 60947, VDE 0660 -25 - 55 °C, Operating range ≤ 0.25 %/K, residual error for T > 40°

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
AMBIENT STORAGE TEMPERATURE - MAX	80 °C
CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Electrical rating

RATED FREQUENCY - MIN	50 Hz
RATED FREQUENCY - MAX	60 Hz
RATED OPERATIONAL CURRENT (IE)	20 A
RATED OPERATIONAL POWER AT AC-3, 220/230 V, 50 HZ	5.5 kW
RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ	9 kW
RATED OPERATIONAL VOLTAGE (UE) - MIN	690 V
RATED OPERATIONAL VOLTAGE (UE) - MAX	690 V
RATED UNINTERRUPTED CURRENT (IU)	20 A

Terminal capacities

TERMINAL CAPACITY (SOLID)	1 x (1 - 6) mm ² 2 x (1 - 6) mm ²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	18 - 10
STRIPPING LENGTH (MAIN CABLE)	10 mm
TIGHTENING TORQUE	1.7 Nm, Screw terminals, Main cable

Short-circuit rating

SHORT-CIRCUIT CURRENT RATING (GROUP PROTECTION)	10 kA, 600 V High Fault, Fuse, SCCR (UL/CSA) with 150 A, 600 V High Fault, Fuse, SCCR (UL/CSA) 10 kA, 600 V High Fault, CB, SCCR (UL/CSA) with 125 A, 600 V High Fault, CB, SCCR (UL/CSA) 18 kA, 600 V High Fault, Fuse with CL, SCCR (UL/CSA) with 600 A, 600 V High Fault, Fuse with CL, SCCR (UL/CSA) 18 kA, 600 V High Fault, CB with CL, SCCR (UL/CSA) with 600 A, 600 V High Fault, CB with CL, SCCR (UL/CSA) 18 kA, 480 V High Fault, CB, SCCR (UL/CSA) with 600 A, 480 V High Fault, CB, SCCR (UL/CSA) 18 kA, 480 V High Fault, Fuse, SCCR (UL/CSA) with 600 A, 480 V High Fault, Fuse, SCCR (UL/CSA)
SHORT-CIRCUIT RELEASE	Basic device fixed 15.5 x I _u ± 20% tolerance 310 A, I _{rm}
RATED SHORT-CIRCUIT BREAKING CAPACITY ICS AT 400 V AC	38 kA
RATED SHORT-CIRCUIT BREAKING CAPACITY ICU AT 400 V AC	50 kA
RATED SHORT-CIRCUIT	10 kA

Motor rating

ASSIGNED MOTOR
POWER AT 230/240 V, 60
HZ, 1-PHASE 3 HP

ASSIGNED MOTOR
POWER AT 575/600 V, 60
HZ, 3-PHASE 15 HP

Design verification

EQUIPMENT HEAT
DISSIPATION, CURRENT-
DEPENDENT PVID 5.82 W

HEAT DISSIPATION
CAPACITY PDISS 0 W

HEAT DISSIPATION PER
POLE, CURRENT-
DEPENDENT PVID 1.9 W

RATED OPERATIONAL
CURRENT FOR SPECIFIED
HEAT DISSIPATION (IN) 20 A

STATIC HEAT
DISSIPATION, NON-
CURRENT-DEPENDENT
PVS 0 W

BREAKING CAPACITY ICU
AT 440 V AC

RATED SHORT-CIRCUIT
BREAKING CAPACITY ICS 3 kA
AT 440 V AC

RATED SHORT-CIRCUIT
BREAKING CAPACITY ICU 3 kA
AT 500 V AC

RATED SHORT-CIRCUIT
BREAKING CAPACITY ICS 3 kA
AT 500 V AC

RATED SHORT-CIRCUIT
BREAKING CAPACITY ICU 3 kA
AT 690 V AC

RATED SHORT-CIRCUIT
BREAKING CAPACITY ICS 1 kA
AT 690 V AC

Trip blocks

OVERLOAD RELEASE
CURRENT SETTING - MIN 16 A

OVERLOAD RELEASE
CURRENT SETTING - MAX 20 A

Do pobrania

CHARACTERISTIC CURVE [eaton-manual-motor-starters-characteristic-characteristic-curve-008.eps](#)

DEKLARACJE ZGODNOŚCI [DA-DC-00004890.pdf](#)

INSTRUKCJE MONTAŻU [IL034046ZU](#)

MODELE ECAD [ETN.189906.edz](#)

MODELE MCAD [DA-CD-pkzm0](#)

[DA-CS-pkzm0](#)

RYSUNKI [eaton-manual-motor-starters-pkz-dimensions-002.eps](#)

[eaton-manual-motor-starters-pkz-dimensions.eps](#)

[eaton-manual-motor-starters-pkz-dimensions-003.eps](#)

[eaton-manual-motor-starters-circuit-breaker-pkzm0-3d-drawing.eps](#)

[eaton-manual-motor-starters-pkzm0-3d-drawing-008.eps](#)

SCHEMATY POŁĄCZEŃ

[eaton-manual-motor-starters-transformer-pkzm0-wiring-diagram.eps](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATA:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. Wszelkie prawa zastrzeżone.